



GST. 1018
E.Z. 1507

GST 77/167

LEGENDE

1	Deckung wie Bestand	Lattung Kontertattung Sparren 16,00cm 5,00cm 3,00cm	2x 8,00cm 2x 1,50cm
2	Trockenestrich	Konstruktion dazw. WD - Filz Folie / Dampfsperre Schalung GFK - Platten	2,50cm 2x 1,50cm
3	FB - Belag Estrich TDP 45/40 FT - Decke	2,00cm 6,00cm 4,00cm 18,00cm	2,00cm 6,00cm 4,00cm
4	FB - Belag Estrich TDP 45/40 Pappe geflämmt Beton bewährt WD exdrud Polyst. Sandausgleich Rolleierung / Schüttung	2,00cm 6,00cm 4,00cm 3 lagig 20,00cm 10,00cm	2,00cm 6,00cm 4,00cm 3 lagig 20,00cm 10,00cm
5	Vollwärmeschutz Porotherm - Ziegel Thermoputz	6,00cm 30,00cm 3,00cm	6,00cm 30,00cm 3,00cm
6	Vollwärmeschutz Ziegel (Bestand) WD - Anplankung	6,00cm 25,00cm 8,00cm	6,00cm 25,00cm 8,00cm

